Waste Oil Heater Competitor Comparison Chart



	design to the second se	clean burn	FIRELAKE 2			REZNOR
Heat Rise	110°F	60°F	60°F	60°F	60°F	60°F
Longest Maintenance Cycle	1000 Hours	500 Hours	1000 Hours	400 Hours	700 Hours	700 Hours
Range of Burnable Oils	No.2 to 90W + synthetics	No.2 to 50W	No.2 to 50W	No.2 to 50W	No.2 to 90W	No.2 to 50W
Burns Synthetic Oils	Yes	No	No	No	Yes	No
Adjustments/ Maintenance Required Weekly*	Νο	No	Yes	Yes	Yes	Yes
Ease of Maintenance	Swing Out Burner, 1 Large Tube	9+ Small Tubes	1 Large Tube, Burner Gun	8+ Small Tubes	1 Large Tube, 3 Smaller Tubes	1 Large Tube, 3 Smaller Tubes
Parts Warranty	2 years [†]	1 Years	1 Year	1 Year	3 Years	1 Year
On Board Air Compressor (Doesn't Use Shop Air)	Standard	Optional	Optional	Optional	Standard	Standard - Piston Compressor
Low Fuel Cut-Off	Standard	No	No	No	Optional	No
Metering Pump	Standard	Optional	Optional	No	Optional	Standard
Money Back Guarantee	Yes	No	No	No	No	No

* According to manufacturers operations manual.

[†] One year warranty standard. Second year warranty requires product registration within 30 days of product receipt.

