



LS-300D PRO SERIES

ENGINEERED FOR RELIABILITY BUILT FOR PERFORMANCE

Built from customer feedback for easier installation, easier maintenance, and our best performance yet.



**Contact Lanair
to calculate
which heater is
right for you.**



**Output up to
300,000 BTUs.**



**Burns 100%
Synthetic Oil**
*along with other fluids see
full specs on backside.*



**UNBOX. INSTALL.
FREE HEAT.**

This system is engineered for reliability and reduced maintenance, making operation and upkeep simpler.

With easier priming, a standard metering pump, and a flooded pump design that minimizes suction leak risk, performance starts strong and stays consistent. Routine maintenance is streamlined with a spin-on filter, an easier-to-clean preheater, and a chamber built with upgraded materials for improved corrosion resistance and easier cleaning to maintain performance.

Fewer adjustments and a longer service interval further reduce hands-on time. Installation is straightforward with a complete package that includes the tank, chimney, mounting, plumbing, and hardware. Flexible configuration options, including reversible air and chimney outlets, along with a larger 250-gallon tank, round out a system designed for durability and convenience.

**APPROVED BY
YOUR CHEAPER
HEATING BILL**



4109 Capital Circle
Janesville, WI 53546

**HEATING WITH
WASTE OIL
SINCE 1976**

Follow Us



www.lanair.com

(800) 562-5504

sales@lanair.com

LS-300D PRO SERIES WASTE OIL HEATER



ENGINEERED FOR RELIABILITY
BUILT FOR PERFORMANCE

SPECIFICATIONS

HEAT RANGE	UP TO 300,000 BTU
* VARIABLE BASED ON FUEL TYPE.	
FUEL INPUT	2 GPH
FUEL TYPE	USED CRANKCASE OIL UP TO 50 WT, USED AUTOMATIC TRANSMISSION FLUID, #2 FUEL OIL
TANK CAPACITY	250 GALLONS
ELECTRICAL REQUIREMENT	120 VAC 60 Hz 25 AMPS
CABINET DIMENSIONS (L x W x H)	85" x 26" x 26"
HANGING WEIGHT	420 LBS
FAN STYLE	BLOWER
CHIMNEY PIPE	8" CLASS A
* STANDARD CHIMNEY PACKAGE IS FOR 14' CEILINGS. CONTACT LANAIR FOR OTHER APPLICATIONS.	
AIR PRESSURE	2.0 CFM @ 30 PSI REGULATED TO 12-16 PSI
* AIR PRESSURE REGULATOR IS INCLUDED. REGULATED AIR SOURCE MUST BE SUPPLIED BY THE CUSTOMER.	
DUCTABLE	YES *14" x 14" MINIMUM DUCT OPENING.
CHIMNEY AND AIR OUTLET	REVERSIBLE
OPTIONAL COMPRESSOR REQUIREMENT	30 AMP BREAKER WITH 10 GA WIRE REQUIRED

HEATING AREA CAN BE CALCULATED BASED ON INSTALLATION.



34"

96"

OVERALL DIMENSIONS



EASY
MAINTENANCE



HIGH
AIRFLOW



DURABLE
CONSTRUCTION



FLEXIBLE
FUEL



4109 Capital Circle
Janesville, WI 53546

HEATING WITH
WASTE OIL
SINCE 1976

Follow Us
f o y

www.lanair.com
(800) 562-5504
sales@lanair.com