Mautozone AC519

A/C Service Station

AC519 is a fully automatic intelligent automobile air conditioning maintenance equipment that integrates functions such as disassembly-free cleaning, refrigerant recovery, filling, and vacuuming. It can effectively improve the problems of poor air conditioning cooling effect, large compressor load, high noise, and high fuel consumption.

- More scientific spatial structure layout
- New integrated oil and gas separation module
- Efficient and stable pipeline logic patent
- Clearer control logic and user experience
- Massive refrigerant database





The new patented pipeline logic design and scientifically integrated oil and gas separation module bring more efficient and stable working conditions.

Features

- 1. Equipped with automobile refrigerant model database, no manual setting is required.
- 2. Supports two refrigerants: R134A or R1234YF.
- 3. It has forward, reverse, and pulse cleaning functions, and the cleaning effect is obvious good.
- 4. The automatic mode can complete operations such as cleaning, recycling, vacuuming, filling refrigeration oil, and refrigerant with one click. Each function can also be executed independently.
- 5. Built-in printer supports printing materials, working hours, and other information.

Functions

- 1. Air-conditioning pipeline cleaning: Clean the air-conditioning pipelines, remove sludge, powder and other impurities inside the pipelines, replace the refrigeration oil more thoroughly, improve compressor lubrication, and improve the refrigeration performance of the air-conditioning system.
- 2. Refrigerant recovery: The refrigerant in the automobile air conditioning system is purified and regenerated and then recycled into the working tank to meet the standards for reuse.
- 3. Vacuuming: Achieve vacuuming of air conditioning pipelines and equipment pipelines.
- 4. Refrigeration oil filling: supports manual/automatic filling, and realizes intelligent and precise filling through the built-in electronic scale.
- **5. Refrigerant filling:** Add refrigerant to the vehicle according to the set filling amount.
- 6. Automatic mode: According to the set parameters, automatically perform cleaning, recovery, vacuuming, filling of refrigeration oil, and Inject refrigerant and other operations.
- 7. Database: Equipped with automobile refrigerant model database, supports database calling, no manual setting is required.
- **8. Print:** Supports printing of device execution results.

Parameters

power supply	AC110V/AC220V 50Hz/60Hz	
Main Engine Power	700W	
Working temperature	10~50°C	
Electronic scale accuracy	±10g	

Recycling capacity	Gaseous state:400g/min	Liquid state: 700g/min
Vacuum pump capacity		2pa
Tank		12L
Filling rate		800g/min



