

Please read and save these instructions. Read through this owner's manual carefully before using product. Protect yourself and others by observing all safety information, warnings, and cautions. Failure to comply with instructions could result in personal injury and/or damage to product or property. Please retain instructions for future reference.



18 GALLON UPRIGHT PORTABLE OIL DRAIN

FOR CUSTOMER SERVICE

Technical Question?

CALL 1-866-458-2472
customerservice@oem-tools.com

UNPACKING

After unpacking the unit, inspect carefully for any damage that may have occurred during transit. Check for loose, missing, or damaged parts. If any damage is observed, a shipping damage claim must be filed with the carrier. DO NOT use the OEMTOOLS™ 18 Gallon Upright Portable Oil Drain if broken, bent, cracked or damaged parts (including labels) are noted. Any 18 Gallon Upright Portable Oil Drain that appears damaged in any way, operates abnormally or is missing parts should be removed from service immediately. If you suspect that the 18 Gallon Upright Portable Oil Drain was subjected to shock load (a load that was dropped suddenly, unexpectedly, etc.), immediately discontinue use until it has been checked by a factory authorized service center.



▲ WARNING

The following safety information is provided as a guideline to help you operate your 18 Gallon Upright Portable Oil Drain under the safest possible conditions. Any tool or piece of equipment can be potentially dangerous to use when safety or safe handling instructions are not known or not followed. The following safety instructions are to provide the user with the information necessary for safe use and operation. Please read and retain these instructions for the continued safe use of your tool. Failure to follow instructions listed below may result in serious injury. In addition, make sure that anyone who uses the equipment understands and follows these safety instructions as well.

Explanation of Safety Signal Words

▲ WARNING: Indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury.

▲ CAUTION: Indicates a potentially hazardous situation which, if not avoided, may result in minor or moderate injury.

CAUTION: Used without the safety alert symbol indicates a potentially hazardous situation which, if not avoided, may result in property damage.

NOTES: Provide clarity and helpful information.

Thank you very much for choosing an OEMTOOLS™ Product!

For future reference, please register your new tool at www.oem-tools.com and complete the owner's record below:

Model: _____ **Purchase Date:** _____

Save the receipt, warranty and these instructions. It is important that you read the entire manual to become familiar with this product before you begin using it. This product is designed for certain applications only. OEMTOOLS™ cannot be responsible for issues arising from modification. We strongly recommend that this product is not modified and/or used for any application other than that for which it was designed. If you have any questions relative to a particular application, DO NOT use the product until you have first contacted customer service to determine if it can or should be performed on the product.



18 GALLON UPRIGHT PORTABLE OIL DRAIN

! IMPORTANT INSTRUCTIONS AND SAFETY RULES

1. Know your tool. Read this manual carefully. Learn the tool's applications and limitations, as well as potential hazards specific to it.
2. Keep work area clean and well lit. Cluttered or dark work areas invite accidents.
3. Keep children away. All children should be kept away from the work area. Never let a child handle a tool without strict adult supervision.
4. DO NOT operate this tool if under the influence of alcohol or drugs. Read warning labels on prescriptions to determine if your judgment or reflexes are impaired while taking drugs. If there is any doubt, DO NOT attempt to operate.
5. Use safety equipment. Eye protection should be worn at all times when operating this tool. Use ANSI approved safety glasses. Everyday eyeglasses are NOT safety glasses. Dust mask, non-skid safety shoes, hard hat or hearing protection should be used in appropriate conditions.
6. Wear proper apparel. Loose clothing, gloves, neck-ties, rings, bracelets or other jewelry may present a potential hazard when operating this tool. Keep all apparel clear of the tool.
7. DO NOT overreach. Keep proper footing and balance at all times when operating this tool.
8. Check for damage. Check your tool regularly. If part of the tool is damaged, it should be carefully inspected to make sure that it can perform its intended function correctly. If in doubt, the part should be repaired. Refer all servicing to a qualified technician. Consult your dealer for advice.
9. Keep away from flammables. DO NOT attempt to operate this tool near flammable materials or combustibles. Failure to comply may cause serious injury or death.
10. Store idle tools out of the reach of children and untrained persons. Tools may be dangerous in the hands of untrained users.
11. Maintain tools with care.
12. Keep tools dry and clean.
13. Properly maintained tools are less likely to bind and are easier to control. DO NOT use a damaged tool. Tag damaged tools "DO NOT use" until repaired.
14. Check for misalignment or binding of moving parts, breakage of parts, and any other condition that may affect the tool's operation.
15. If damaged, have the tool serviced before using. Many accidents are caused by poorly maintained tools.
16. Use only accessories that are recommended by the manufacturer for your model. Accessories that may be suitable for one tool may become hazardous when used on another tool.
17. Tool service must be performed only by qualified repair personnel. Service or maintenance performed by unqualified personnel could result in a risk of injury.
18. When servicing a tool, use only identical replacement parts. Use of unauthorized parts or failure to follow maintenance instructions may create a risk of injury.
19. Maintain a safe working environment. Keep the work area well lit. Make sure there is adequate surrounding workspace. Keep the work area free of obstructions, grease, oil, trash, and other debris. Do not use this product in a damp or wet location.
20. Maintain labels and nameplates on this product. These carry important information. If unreadable or missing, contact OEMTOOLS™ for a replacement.
21. Keep the handle dry, clean, and free from brake fluid, oil, and grease.
22. Before use, read and understand all warnings, safety precautions, and instructions as outlined in the vehicle manufacturer's service manual. It is beyond the scope of this manual to properly describe the correct procedure and test data for each vehicle.
23. Always perform vehicle service in a properly ventilated area. Never run an engine without proper ventilation for its exhaust. Stop work and take necessary steps to improve ventilation in the work area if you develop momentary eye, nose, or throat irritation as this indicates inadequate ventilation.
24. Engine parts that are in motion and unexpected movement of a vehicle can injure or kill. When working near moving engine parts, wear snug fit clothing and keep hands and fingers away from moving parts.
25. Keep hoses and tools clear of moving parts. Always stay clear of moving engine parts. Hoses and tools can be thrown through the air if not kept clear of moving engine parts.
26. The unexpected movement of a vehicle can injure or kill. When working on vehicles, always set the parking brake or chock the wheels.
27. Avoid accidental fire and/or explosion. DO NOT smoke near engine fuel and battery components.
28. The warnings, precautions, and instructions discussed in this manual cannot cover all possible conditions and situations that may occur. The operator must understand that common sense and caution are factors which cannot be built into this product, but must be supplied by the operator.
29. For safety purposes and the prevention of damage to expensive components, it is advised that the user have an understanding of basic automotive repair and a working knowledge of automotive systems.
30. We believe the information contained herein to be reliable. However, general technical information is given by us without charge and the user shall employ such information at their own discretion and risk. We assume no responsibility for results or damages incurred from the use of such information in whole or in part. Always refer to specific instructions and technical information supplied by vehicle manufacturer.
31. The manufacturer declines any and all responsibility for damage to vehicles or components if said damage is the result of unskillful handling by the operator or of failure to observe the basic safety rules set forth in the instruction manual.
32. This equipment is intended only for professional use by personnel trained in performing the service functions for which it is has been designed.



18 GALLON UPRIGHT PORTABLE OIL DRAIN

33. This equipment is designed for servicing a variety of engines in a safe, convenient manner. However, differences in engine makes and models may make it impossible to use this equipment as it is intended. DO NOT attempt to force the use of this equipment on an application for which it is not designed to perform.
34. The procedures documented in this manual are to serve as guidelines for the use of this equipment.
35. In addition to these guidelines, always follow the manufacturer's recommended procedures when servicing each unique vehicle.
36. The use of this equipment is simple and straightforward if you follow the instructions. When operating this equipment, use common sense, and only use this 18 Gallon Upright Portable Oil Drain for its intended purpose.

PRODUCT DESCRIPTION

The 18 Gallon Upright Portable Oil Drain is designed to efficiently drain waste oil from a vehicle.

PRODUCT SPECIFICATIONS

Funnel Diameter:	18"
Capacity:	18 Gallons
Adjustable Drain Height:	54" to 70"

CONTENTS

Funnel, upper tube, funnel screw, adjustable tube clamp, lower tube, adjustable tank clamp, oil tank, drain cap and (4) casters

SPECIFIC SAFETY INSTRUCTIONS AND WARNINGS

1. Not designed for use with gasoline.
2. DO NOT exceed rated capacity. Overloading can cause damage or failure of the oil drain.
3. Keep hands clear of all adjustment points during assembly, usage and transport.
4. Only use oil drain on dry, oil/grease free, level, ground surfaces. Ensure the surface can support the weight of the drain at capacity.
5. Wear protective clothing, gloves and eyewear while working with used fluids.
6. Allow engine to cool before servicing vehicle.
7. DO NOT leave oil drain unattended while operating or evacuating oil.
8. Never use or store near open flames or heat sources.
9. DO NOT leave under automotive lift while lowering the vehicle to the ground surface.

DISPOSAL

At the end of the useful life of the 18 Gallon Upright Portable Oil Drain, dispose of the components according to all state, federal and local regulations.

ASSEMBLY

1. Remove all contents from the package.
2. Insert the funnel (A) into the upper tube (B) and use the small tightening screw (C) to tighten the funnel into place.
3. Place the adjustable tube clamp (D) at the midpoint of the upper tube (B); the positioning of this clamp determines the height of the drain.
4. Insert at least 4" of the lower tube (E) into the oil tank (F) and tighten into place using the adjustable tank clamp (G).
5. Screw the drain cap (H) onto the oil tank (F); and turn the drain valve handle (I) clockwise until finger tight.
6. Insert the upper tube (completed upper assembly from Step 3) into the lower tube (completed lower assembly from Step 5).

OPERATION

1. While supporting the upper assembly, slightly unscrew the tank clamp (G) and lower the bottom tube into the tank.
2. Squeeze the adjustable tube clamp (D) and slide to the top of the upper tube while supporting the upper assembly; slowly lower the upper tube into the lower tube.
3. Move the oil drain under the raised vehicle, ensuring the funnel is centered directly below the engine oil drain plug.
4. Using the adjustable tube (D) and tank clamps (G), raise the funnel until approximately 4" below the engine oil drain plug.
5. Remove the engine oil drain plug and allow the used oil to completely drain into the funnel.
6. When complete, follow all federal, state and local laws for oil disposal and recycling procedures.

MAINTENANCE

Periodically inspect the oil drain. Ensure all parts move freely. Apply lubrication as needed.

STORAGE

Store the portable oil drain in an upright position and in a clean, dry area. Do not store near flammable items or open flames. This could result in injury or explosion or property damage.




18 GALLON UPRIGHT PORTABLE OIL DRAIN

Parts List

Figure	Description	Quantity
A	Funnel	1
B	Upper Tube	1
C	Small Tightening Screw	1
D	Adjustable Tube Clamp	1
E	Lower Tube	1
F	Oil Tank	1
G	Adjustable Tank Clamp	1
H	Drain Cap	1
I	Drain Valve Handle	1

Parts Diagram



NOTE: Not all components of the 18 Gallon Upright Portable Oil Drain are replacement items, but are illustrated as a convenient reference for location and position in the assembly sequence. The manufacturer and/or distributor have provided the parts list and assembly diagram in this manual as a reference tool only. Neither the manufacturer nor distributor makes any representation or warranty of any kind to the buyer that he or she is qualified to make any repairs to the

product, or that he or she is qualified to replace any parts of the product. In fact, the manufacturer and/or distributor expressly states that all repairs and parts replacements should be undertaken by certified and licensed technicians, and not by the buyer. The buyer assumes all risk and liability arising out of his or her repairs to the original product or replacement parts thereto, or arising out of his or her installation of replacement parts thereto.

OEMTOOLS™ Limited 90 Day WARRANTY

Within 90 days from the original date of purchase of this OEMTOOLS™ product, if you find any defect in material or workmanship, through normal usage, return it to the place of purchase, or to OEMTOOLS™ for repair or replacement at our discretion. In order to obtain this service, send your tool and proof of purchase, transportation pre-paid, to OEMTOOLS™ Q.A. Dept., 3580 E. Raines Road #3, Memphis, TN 38118. We will not be responsible for lost or damaged goods during transportation; please insure your package. If our inspection verifies the defect, we will either repair or replace the product at our election, or we may elect to refund the purchase price if we cannot readily and quickly provide you with a replacement. We will return repaired products at our expense, but if we determine there is no defect, or that the defect resulted from causes not within the scope of our warranty, then you must bear the cost of returning the product.

OEMTOOLS™ does not provide warranty for products labeled other than OEM® or OEMTOOLS™. OEMTOOLS™ will not provide any warranty for products subjected to abnormal use. Abnormal use includes, but is not limited to, abuse, accident, alteration, neglect, and unauthorized or unreasonable use or repairs. This warranty does not cover bits, blades, files, batteries, or calibration. We recommend that you maintain your tools and sharpen or replace blades, bits, files, and batteries as necessary. OEMTOOLS™ reserves the right to make any changes in construction or design at any time without any obligation in incorporating such changes to tools or equipment previously sold.

OEMTOOLS™ makes every effort to ensure that its products meet high quality and durability standards, and warrants to the original purchaser that this product is free from defects in materials and workmanship for the period of 90 days from the date of purchase. This warranty does not apply to damage due directly or indirectly to misuse, abuse, negligence or accidents, repairs or alterations outside our facilities, criminal activity, improper installation, normal wear and tear or to lack of maintenance.

We shall in no event be liable for death, injuries to persons or property, or for incidental, contingent, special or consequential damages arising from the use of our product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation of exclusion may not apply to you. THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

Don't forget to register your new OEMTOOLS™ product at www.oem-tools.com.

CONTACT US

3580 E. Raines Road, Suite 3, Memphis, TN 38118
Tel: 1-866-458-2472
www.oem-tools.com